


## Áttekintés

## Termék információ

**8EDGKG-3.81-10020002659**

Pluggable terminal blocks, Rated current: 10A. Rated voltage  
(III/3) : 130V, pitch: 3.81mm, Color: gray, Contact surface : Tin

## A termék előnyei

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Cage clamp connection technology, fast wiring
- ☒ Universal installation method, suitable for various situations

## Termék tanúsítás



## Műszaki adatok

## Termékrajz

## 3D modell

□

## Connection capacity

|                                  |                        |
|----------------------------------|------------------------|
| Conductor cross section solid    | 0.2~1.5mm <sup>2</sup> |
| Conductor cross section flexible | 0.2~1.5mm <sup>2</sup> |
| AWG                              | 28~14AWG               |
| Strip length                     | 6mm                    |

## Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 10A  |
| Rated current (D) | 10A  |

Electrical parameters IEC

|                            |       |
|----------------------------|-------|
| Rated voltage              | 130V  |
| Rated voltage(III/3)       | 130V  |
| Rated current              | 10A   |
| Rated surge voltage(III/3) | 2.5KV |

Item properties

|                      |                        |
|----------------------|------------------------|
| Connection direction | 0°                     |
| Connection method    | spring-cage connection |
| Pitch                | 3.81mm                 |
| Number of potentials | 2                      |
| Pluggable or not     | Yes                    |
| Number of rows       | 1                      |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | Copper alloy              |
| Contact point metal surface | tin-plated                |
| Contact zone metal surface  | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~105℃ |
|---------------------------------|-----------|

## Melléklet

### Accessories

|               |   |
|---------------|---|
| Coding strip  | / |
| Bridge        | / |
| Marking strip | / |
| Others        | / |

### Tool

|                |   |
|----------------|---|
| Operating tool | / |
| Screwdriver    | / |

## Üzleti adatok

|                                      |             |
|--------------------------------------|-------------|
| Rendelészám                          | 10020002659 |
| Csomagolási egység                   | 180         |
| Minimális rendelési mennyiség        | 30          |
| A termékek súlya (csomagolás nélkül) | 2.25        |