

Przegląd

Informacje o produkcie



DG262-5.0-10060001606

PCB spring terminal blocks, Rated current: 32A. Rated voltage
(III/2) : 320V, pitch: 5.0mm, Color: gray, Contact surface : Tin

Zalety produktu

- ☒ Universal installation method, suitable for various situations
- ☒ 45° connection can realize multi-row layout on PCB
- ☒ Different poles can be combined through the side lock

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~4mm²

Conductor cross section flexible

0.2~4.0mm²

AWG

28~12AWG

Strip length

9mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)	20A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated voltage(III/3)	320V
Rated current	32A
Rated voltage(III/2)	320V
Rated voltage(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	spring-cage connection
Pitch	5mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated

Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL 1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Akcesoria

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Dane biznesowe

numer zamówienia	10060001606
Jednostka opakowania	200
Minimalna ilość zamówienia	30
Waga produktów (bez opakowania)	2.527