

Przegląd

Informacje o produkcie

**DG331-5.0-10040001193**

Pluggable terminal blocks, Rated current: 12A, Rated voltage (III/2) 250V, Cross section: 2.5mm², pitch: 5.0mm, connector method: screw connector with wire protection, Color: green, Contact surface: Tin

Zalety produktu

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ Fixed screw connection technology, safe and reliable

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D



Connection capacity

Conductor cross section solid	1.0~2.5mm ²
Conductor cross section flexible	1.0~2.5mm ²
AWG	28~14AWG
Torque	0.5N.m
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	10A

Electrical parameters IEC

Rated voltage	250V
Rated current	12A
Rated voltage(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Connection direction	0°
Connection method	Screw connection with wire protection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Akcesoria

Tool

Screwdriver	0.5x3.0mm, Slotted screwdriver
Operating tool	/

Accessories

Coding strip	/
Bridge	DG019-5.0
Marking strip	/
Others	/

Dane biznesowe

numer zamówienia	10040001193
Jednostka opakowania	#N/A
Minimalna ilość zamówienia	30
Waga produktów (bez opakowania)	#N/A