

Przegląd

Informacje o produkcie

**DG2002-4.0-300A(H)-10060001736**

PCB spring terminal blocks, Rated current: 9A. Rated voltage (III/2): 160V, pitch: 4.0mm, Color: White, Contact surface: Tin

Zalety produktu

- ✓ PUSH-IN connection technology, fast wiring
- ✓ Suitable for SMT welding process
- ✓ Compact structure, saving installation space

Certyfikacja produktu



Dane techniczne

Rysunek produktu

Model 3D

□

Electrical parameters UL

Rated current (B)

9A

Electrical parameters IEC

Rated voltage

160V

Rated voltage(III/3)

32V

Rated current

9A

Rated voltage(III/2)

160V

Rated voltage(II/2)

160V

Rated surge voltage(III/3)

4KV

Rated surge voltage(III/2)

4KV

Rated surge voltage(II/2)	4KV
---------------------------	-----

Item properties

Connection direction	0°
Pitch	4mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1977
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~130℃
---------------------------------	-----------

Aksesoria

Accessories

Coding strip	/
Bridge	DG027-4.0
Marking strip	/
Others	/

Tool

Operating tool	DG028
----------------	-------

Screwdriver

/

Dane biznesowe

numer zamówienia	10060001736
Jednostka opakowania	0
Minimalna ilość zamówienia	30
Waga produktów (bez opakowania)	0.64