

## Áttekintés

### Termék információ



## DG271R-7.5-10060001433

PCB spring terminal blocks, Rated current: 41A. Rated voltage  
(III/2) : 1000V, pitch: 7.5mm, Color: green, Contact surface : Tin

### A termék előnyei

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method, suitable for various situations

### Termék tanúsítás



## Műszaki adatok

### Termékrajz

### 3D modell

□

### Processing notes

Process

Wave soldering/manual soldering

### Connection capacity

Conductor cross section solid

0.2~6mm<sup>2</sup>

Conductor cross section flexible

0.2~6.0mm<sup>2</sup>

AWG

24~8AWG

Strip length

14mm

### Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

|                   |     |
|-------------------|-----|
| Rated current (B) | 40A |
| Rated current (D) | 10A |

#### Electrical parameters IEC

|                            |       |
|----------------------------|-------|
| Rated voltage              | 1000V |
| Rated voltage(III/3)       | 630V  |
| Rated current              | 41A   |
| Rated voltage(III/2)       | 1000V |
| Rated voltage(II/2)        | 1000V |
| Rated surge voltage(III/3) | 6KV   |
| Rated surge voltage(III/2) | 6KV   |
| Rated surge voltage(II/2)  | 6KV   |

#### Item properties

|                      |                               |
|----------------------|-------------------------------|
| Connection direction | 0°                            |
| Type of installation | PCB welding                   |
| Pin arrangement      | Double-row in a straight line |
| Connection method    | Push-in spring connection     |
| Pitch                | 7.5mm                         |
| Number of potentials | 1                             |
| Pluggable or not     | no                            |
| Number of rows       | 1                             |

#### Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |

|                           |         |
|---------------------------|---------|
| Insulation Materials      | PA66    |
| Insulating material group | I       |
| Flammability rating       | UL94V-0 |

#### Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC60947/UL 1059 |
|--------------------|------------------|

#### Environmental data

|                                 |             |
|---------------------------------|-------------|
| Ambient temperature (operation) | -40°C~105°C |
|---------------------------------|-------------|

#### Melléklet

##### Accessories

|               |   |
|---------------|---|
| Coding strip  | / |
| Bridge        | / |
| Marking strip | / |
| Others        | / |

##### Tool

|                |   |
|----------------|---|
| Operating tool | / |
| Screwdriver    | / |

#### Üzleti adatok

|                                      |             |
|--------------------------------------|-------------|
| Rendelészám                          | 10060001433 |
| Csomagolási egység                   | 100         |
| Minimális rendelési mennyiség        | 30          |
| A termékek súlya (csomagolás nélkül) | 4.8         |