

Áttekintés

Termék információ

**8EDGKF-5.0-10020002650**

Pluggable terminal blocks, Rated current: 20A. Rated voltage
(III/3) : 320V, pitch: 5.0mm, Color: gray, Contact surface : Tin

A termék előnyei

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Cage clamp connection technology, fast wiring
- ☒ Universal installation method, suitable for various situations

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

□

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
AWG	22~14AWG
Strip length	9mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	150V
Rated voltage (D)	300V

Rated current (B)	15A
Rated current (D)	10A
Rated current (C)	15A

Electrical parameters IEC

Rated voltage	320V
Rated voltage(III/3)	320V
Rated current	20A
Rated surge voltage(III/3)	4KV

Item properties

Connection direction	90°
Connection method	spring-cage connection
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)

-40 °C ~105 °C

Melléklet

Accessories

Coding strip	/
Bridge	DG018-5.0
Marking strip	/
Others	/

Tool

Operating tool	DG010
Screwdriver	/

Üzleti adatok

Rendelészám	10020002650
Csomagolási egység	100
Minimális rendelési mennyiség	30
A termékek súlya (csomagolás nélkül)	5.23