

Áttekintés

Termék információ



9EDGK-7.5-10020001573

Pluggable terminal blocks, Rated current: 20A. Rated voltage
(III/2) : 630V, pitch: 7.5mm, Color: black, Contact surface : Tin

A termék előnyei

- ☒ Cage clamp pluggable connection technology, reliable wiring
- ☒ Self-locking structure with sound prompt, safe to use

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell

□

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
AWG	28~12AWG
Strip length	8mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	600V
Rated current (B)	16A

Rated current (D)	5A
Rated current (C)	16A

Electrical parameters IEC

Rated voltage	630V
Rated voltage(III/3)	500V
Rated current	20A
Rated voltage(III/2)	630V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	0°
Connection method	spring-cage connection
Pitch	7.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	Gold plate
Insulation Materials	PA66
Insulating material group	II

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC61984/ UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Melléklet	
Tool	
Screwdriver	/
Operating tool	DG010
Accessories	
Coding strip	/
Bridge	DG018-7.5
Marking strip	/
Others	/

Üzleti adatok	
Rendelészám	10020001573
Csomagolási egység	100
Minimális rendelési mennyiség	30
A termékek súlya (csomagolás nélkül)	4.402