

Overview

Product information



Ultra thin Push-in connection relay Socket-DPRF-05A-E1-00A(H)-30020000121

DPRF Relay Socket, used for 1 PDT relay, push-in connection

Product advantages

- ☒ Ultra thin Push-in relay Socket
- ☒ Safe isolation between coils and contacts
- ☒ 6A maximum switching current

Product certification



Technical data

Product drawing

3D model

□

Dimension

width	6.2mm
length	96.5mm
Depth including bracket	81mm

Environmental data

Ambient temperature (operation)	-40℃～+70℃
Ambient temperature (storage / transport)	-40℃～+70℃

Technical data

Rated voltage UN	277V
------------------	------

Rated current IN	6A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
Connection method	PUSH-IN connection
Stripping length	8-12mm
Cross section of flexible conductor	0.25-2.5mm ²
Connectable guide cross section AWG	22-14AWG

Connection data 2

Connection name	Output
Stripping length	8-12mm
Cross section of flexible conductor	0.25-2.5mm ²
Connectable guide cross section AWG	22-14AWG
Connection method	PUSH-IN connection

Accessories

Accessory

Bridge	DBA20-6-12-00A(H) DBA20-6-13-00A(H) DBA20-6-16-00A(H)
--------	---

Business data

Order number	30020000121
Packing unit	25 SKT
Minimum order quantity	25 SKT

Products weight (without packaging)	22g
-------------------------------------	-----