

概要

製品情報



DGBSC-PG01M/4-10080000742

Feed Through Terminal Blocks, Rated current: 32A, Contact surface: Tin, Connection method: PUSH-IN connection

製品の特長

- ☒ Push-In, spring connection more vibration resistance
- ☒ Special structure coding, wiring guide identification
- ☒ With a fixed buckle, the connection is more secure and stable
- ☒ IP20 High protection level

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Strip length

10~11mm

Connection capacity

Conductor cross section solid

0.5~4mm²

Conductor cross section flexible

0.5~4.0mm²

AWG

20~12AWG

Electrical parameters IEC

Rated voltage(III/3)

250V

Rated current

32A

Rated voltage(III/2)	400V
----------------------	------

UL Electrical parameters

Rated voltage (Use Group B)	600V
Rated current (Use Group B)	20A

Item properties

Connection method	Push-in spring connection
Number of potentials	3
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
---------------------	---------------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

アクセサリ

ビジネスデータ

注文番号	10080000742
パッキングユニット	40
最小注文数量	
1 個あたりの重量（梱包を 含めない）	20.56