

概要

製品情報



DGBSC-SG01/6-10080000630

Building wiring terminals, Rated current: 41A. Rated voltage (III/2): 450V, max. 6 mm², Color: transparent, Contact surface: Tin

製品の特長

- ☒ Rotatable operating handle, easy to operate
- ☒ Suitable for field wiring, saving installation time

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Strip length

13~14mm

Connection capacity

Conductor cross section solid

0.5~6mm²

Conductor cross section flexible

0.5~6.0mm²

AWG

20~10AWG

Electrical parameters UL

Rated voltage (C)

600V

Rated current (C)

30A

Electrical parameters IEC

Rated voltage	450V
Rated current	41A
Rated voltage(III/2)	450V

Item properties

Connection method	Push-in spring connection
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

アクセサリ

ビジネスデータ

注文番号

10080000630

パッキングユニット	400
最小注文数量	
1 個あたりの重量（梱包を 含めない）	5.1