


概要

製品情報



DG126R-5.0-10050000072

PCB terminal blocks, Rated current: 18A, Rated voltage (Ⅲ/2) 250V, Cross section: 2.5mm², pitch: 5.0mm, connector method: screw connector with wire protection, Color: green, Contact surface : Tin

製品の特長

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ Square wiring hole, large wiring capacity
- ☒ Different poles can be combined through the side lock

製品認証



技術データ

製品チャート

3Dモデル

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.75~1.5mm²

Conductor cross section flexible

0.75~1.5mm²

AWG

26~14AWG

Strip length

7mm

Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)	10A
-------------------	-----

Electrical parameters IEC

Rated voltage	250V
Rated current	10A
Rated voltage(III/2)	250V
Rated power frequency voltage(1min)	2KV

Item properties

Connection direction	90°
Type of installation	PCB Soldering
Pin arrangement	Single row in a straight line
Connection method	Screw connection with wire protection
Screwdriver	Slotted screwdriver
screw thread	M2.5
Pitch	5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
Environmental data	
Ambient temperature (operation)	-40℃~105℃

アクセサリ	
Accessories	
Coding strip	/
Bridge	DG019-5.0
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	0.6x3.5mm, Slotted screwdriver

ビジネスデータ	
注文番号	10050000072
パッキングユニット	500
最小注文数量	30
1 個あたりの重量（梱包を 含めない）	1.596