

Panoramica

Informazioni sul prodotto



SA-EBBF-3005-M-L300-00A(H)-25040000002

Male float connector for exchange battery. Rated current: 60A; Rated voltage: 72V DC; Withstand voltage: 1500V AC; Insulation resistance > 500M Ω ; Mechanical life $\geq$ 5000 times; Pull out force > 50N; Operating temperature: -40 ~ 105 $^{\circ}\text{C}$; Salt spray resistance : 72h; Flame retardant grade: UL94-v0; Environmental protection: RoHS.

Vantaggi del prodotto

- ☒ Product interoperability with positive and negative insertion function
- ☒ The floating amount when the product is inserted can compensate for the gap between the car body and the battery
- ☒ The guide post is aligned and inserted, which is convenient and quick

Certificazione del prodotto

RoHS

Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

Series	DA
	DEE
	DQ
	DF

versions

Connection method	Spring cage connection
Female/Male	Male

Dimension	3A
	32A
	6B
	10B
	24B
	32B
Number of positions	48B
	20
	16
	18

Accessori

Dati aziendali	
numero d'ordine	25040000002
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	