

Panoramica

Informazioni sul prodotto



PM-EBS-0004-M-L300-25020000010

Male connector with direct plug in and out. Rated current: 2A; Rated voltage: 48V DC; Withstand voltage: 300V AC; Insulation resistance > 30M Ω; Protection grade meet IP66 when mated; Mechanical life ≥ 100 times; Pull out force > 25N; Operating temperature: - 40 ~ 105 °C; Salt spray resistance : 48h; Flame retardant grade: UL94-v0; Environmental protection: RoHS. Color: Insert insulation - blue.

Vantaggi del prodotto

- ☑ Small structure and high space utilization
- ☑ Plug-and-play error prevention, simple interface
- ☑ Straight plug operation, convenient and quick
- ☑ Different colors of inner core insulator, easy to identify
- ☑ Beautiful appearance, more ergonomic design

Certificazione del prodotto

RoHS

Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

Series

DD

DK

versions

Connection method

Screw connection

Female/Male

Female

16A

Dimension	6B
	10B
	16B
	24B
	48B
Number of positions	8

Accessori

Dati aziendali	
numero d'ordine	25020000010
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	