

## Panoramica

### Informazioni sul prodotto



### PM-EBS-0006-M-L300-25020000009

Male connector with direct plug in and out. Rated current: 2A; Rated voltage: 48V DC; Withstand voltage: 300V AC; Insulation resistance > 30M Ω; Protection grade meet IP66 when mated; Mechanical life ≥ 100 times; Pull out force > 25N; Operating temperature: - 40 ~ 105 °C; Salt spray resistance : 48h; Flame retardant grade: UL94-v0; Environmental protection: RoHS. Color: Insert insulation - black.

### Vantaggi del prodotto

- ☑ Small structure and high space utilization
- ☑ Plug-and-play error prevention, simple interface
- ☑ Straight plug operation, convenient and quick
- ☑ Different colors of inner core insulator, easy to identify
- ☑ Beautiful appearance, more ergonomic design

### Certificazione del prodotto

# RoHS

## Dati tecnici

### Disegno del prodotto

### Modello 3D

□

### Marking

Series

DD

DK

### versions

Connection method

Screw connection

Female/Male

Female

16A

|                     |     |
|---------------------|-----|
| Dimension           | 6B  |
|                     | 10B |
|                     | 16B |
|                     | 24B |
|                     | 48B |
| Number of positions | 12  |

|           |
|-----------|
| Accessori |
|           |

|                                       |             |
|---------------------------------------|-------------|
| Dati aziendali                        |             |
| numero d'ordine                       | 25020000009 |
| Unità di imballaggio                  |             |
| Quantità di ordine minimo             |             |
| Peso dei prodotti (senza imballaggio) |             |