


Panoramica

Informazioni sul prodotto

**DME-005-FS-21020000131**

Heavy-duty insert, Number of contacts: 5, Dimension: 3A, Rated voltage : 400V, Rated current: 16A, Female insert, Cage clamp connector

Vantaggi del prodotto

- ☒ Spring cage connection technology, high vibration resistance;
- ☒ No special tools required, maintenance-free ;
- ☒ Less materials, easy to manage;
- ☒ Modular products, easy to assemble and maintain .

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

classification	Insert
Series	DM

versions

Connection method	Crimping connection
Female/Male	Female
Dimension	1 module
Number of positions	5
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	16A
	400V
Rated pulse voltage	6KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3/6mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Conductor cross sections (mm²)	0.14-2.5mm²
Conductor cross sections(AWG)	26-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessori

Accessories

Screwdriver	/
-------------	---

Dati aziendali	
numero d'ordine	21020000131
Unità di imballaggio	100
Quantità di ordine minimo	5
Peso dei prodotti (senza imballaggio)	17