

Panoramica

Informazioni sul prodotto



SM-EBS-0006-F-L300-25020000011

Female connector with direct plug in and out. Rated current: 2A; Rated voltage: 48V DC; Withstand voltage: 300V AC; Insulation resistance > 30M Ω ; Protection grade meet IP66 when mated; Mechanical life $\geq$ 100 times; Pull out force > 25N; Operating temperature: - 40 ~ 105 $^{\circ}\text{C}$; Salt spray resistance : 48h; Flame retardant grade: UL94-v0; Environmental protection: RoHS. Color: Insert insulation - black.

Vantaggi del prodotto

- ☒ Small structure and high space utilization
- ☒ Plug-and-play error prevention, simple interface
- ☒ Straight plug operation, convenient and quick
- ☒ Different colors of inner core insulator, easy to identify
- ☒ Beautiful appearance, more ergonomic design

Certificazione del prodotto

RoHS

Dati tecnici

Disegno del prodotto

Modello 3D

☐

Marking

Series

DD

DK

versions

Connection method

Screw connection

Female/Male

Female

16A

Dimension	6B
	10B
	16B
	24B
	48B
Number of positions	12

Accessori

Dati aziendali	
numero d'ordine	25020000011
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	