

Panoramica

Informazioni sul prodotto



PM-EBBL-2105-M-25050000003

Straight angle plug with direct plug in and out, rated current:50A; Rated voltage:110V DC; Withstand voltage:500V AC; Insulation resistance > 100M Ω; Protection grade meet IP67 when mated; Mechanical life ≥ 3000 times; Pull out force > 25N; Operating temperature: - 40 ~ 105 °C; Salt spray resistance : 72h; Flame retardant grade:UL94-v0; Environmental protection:RoHS. Color: lock ring - blue.

Vantaggi del prodotto

- ☑ Quick direct plug connection
- ☑ Auditory and visual feedback when plugged in place
- ☑ High plug life
- ☑ Beautiful appearance, more ergonomic design

Certificazione del prodotto

RoHS

Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

classification	Insert
Series	DD
	DDD
	DM

versions

Connection method	Screw connection
-------------------	------------------

Female/Male	Male
Dimension	3A
	32A
	1 module
	6B
	10B
	16B
	24B
	32B
	48B
Number of positions	3
	2
	1

Accessori

Dati aziendali	
numero d'ordine	25050000003
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	