

Panoramica

Informazioni sul prodotto



8EDGD-5.0-10020002055

Pluggable terminal blocks, Rated current: 20A. Rated voltage
(III/3) : 320V, pitch: 5.0mm, Color: gray, Contact surface : Tin

Vantaggi del prodotto

- ☒ PCB welding, plug direction is perpendicular to the PCB
- ☒ Provides anti-touch protection for connection

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection capacity

Strip length

6mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

15A

Rated current (D)

10A

Electrical parameters IEC

Rated voltage

320V

Rated voltage(III/3)

320V

Rated current	20A
Rated surge voltage(III/3)	4KV

Item properties

Connection direction	90°
Connection method	spring-cage connection
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accessori

Accessories

Coding strip	/
--------------	---

Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Dati aziendali

numero d'ordine	10020002055
Unità di imballaggio	1260
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	1.96