

Panoramica

Informazioni sul prodotto



15EDGVC-THR-2.5 Reel package-10030000843

Pluggable terminal blocks, Rated current: 5A. Rated voltage (III/2) : 250V, pitch: 2.5mm, Color: black, Contact surface : Tin

Vantaggi del prodotto

- ☒ Suitable for SMT welding process
- ☒ The plug direction is perpendicular to PCB, Can meet the needs of different connectors

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

150V

Rated current (B)

4A

Electrical parameters IEC

Rated voltage

250V

Rated current

5A

Rated voltage(III/2)

250V

Rated surge voltage(III/2)

2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pitch	2.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~130°C
---------------------------------	-------------

Accessori

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
--------------	---

Bridge	/
Marking strip	/
Others	/

Dati aziendali

numero d'ordine	10030000843
Unità di imballaggio	220
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	0.78