

Panoramica

Informazioni sul prodotto



DG241-2.5-10060002305

PCB spring terminal blocks, Rated current: 6A. Rated voltage
(III/2): 130V, pitch: 2.5mm, Color: Orange, Contact surface: Tin

Vantaggi del prodotto

- ☒ Cage clamp connection technology, fast wiring
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method to ensure a high degree of flexibility in device design

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~0.5mm²

Conductor cross section flexible

0.2~0.5mm²

AWG

28~20AWG

Strip length

6mm

Electrical parameters UL

Rated voltage (B)

150V

Rated current (B)

5A

Electrical parameters IEC

Rated voltage	130V
Rated current	6A
Rated voltage(III/2)	130V
Rated power frequency voltage(1min)	1.25KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	spring-cage connection
Pitch	2.5mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Accessori

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

Tool

Operating tool

/

Screwdriver

/

Dati aziendali

numero d'ordine

10060002305

Unità di imballaggio

600

Quantità di ordine minimo

30

Peso dei prodotti (senza
imballaggio)

0.647