


Panoramica

Informazioni sul prodotto



DG4-10090000001

Through-wall terminal blocks, Rated current: 24A. Rated voltage
(III/2) : 400V, Width: 6.1mm, Color: gray, Contact surface : Tin

Vantaggi del prodotto

- ☒ Screw connection technology, safe and reliable
- ☒ Through-wall installation, free positioning

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection capacity

Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~4.0mm ²
AWG	30~10AWG
Torque	0.5N.m
Strip length	6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	20A

Rated current (D)	10A
-------------------	-----

Electrical parameters IEC

Rated current	
	24A
Rated voltage(III/2)	400V
Rated surge voltage(III/2)	2.5KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M3
Pitch	6.1mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Accessori

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

/

Tool

Operating tool

/

Screwdriver

/

Dati aziendali

numero d'ordine

10090000001

Unità di imballaggio

120

Quantità di ordine minimo

30

Peso dei prodotti (senza
imballaggio)

4.7