


Panoramica

Informazioni sul prodotto



DM-RJ45-F-21020000084

Heavy-duty insert, Number of contacts: 8, Dimension: 1 module Spaces, Rated voltage : 50V, Rated current: 1A, Female insert, Crimping connector

Vantaggi del prodotto

- ✓ Crimping connection technology, applicable to a wide range of wire specifications ;
- ✓ Modular products, easy to assemble and maintain .

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

classification	Insert
Series	DM

versions

Connection method	Crimping connection
Female/Male	Female
Dimension	1 module
Number of positions	8
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	1A
	50V
Rated pulse voltage	0.8KV
Pollution level	3
On the basis of UL /CSARated current	30V
Insulation resistance	≥10000MΩ
Temperature range	-40℃~+85℃
working life-mating cycles	≥500 time

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Accessori

Dati aziendali

numero d'ordine	21020000084
Unità di imballaggio	100
Quantità di ordine minimo	5
Peso dei prodotti (senza imballaggio)	23.8

