

Panoramica

Informazioni sul prodotto



SM-EBS-0002-F-L300-250200000004

Female connector with direct plug in and out. Rated current: 2A; Rated voltage: 48V DC; Withstand voltage: 300V AC; Insulation resistance > 30M Ω ; Protection grade meet IP66 when mated; Mechanical life $\geq$ 100 times; Pull out force > 25N; Operating temperature: - 40 ~ 105 $^{\circ}\text{C}$; Salt spray resistance : 48h; Flame retardant grade: UL94-v0; Environmental protection: RoHS. Color: Insert insulation - red.

Vantaggi del prodotto

- ☒ Small structure and high space utilization
- ☒ Plug-and-play error prevention, simple interface
- ☒ Straight plug operation, convenient and quick
- ☒ Different colors of inner core insulator, easy to identify
- ☒ Beautiful appearance, more ergonomic design

Certificazione del prodotto

RoHS

Dati tecnici

Disegno del prodotto

Modello 3D

☐

Marking

Series

DD

DK

versions

Connection method

Screw connection

Female/Male

Female

16A

Dimension	6B
	10B
	16B
	24B
	48B
Number of positions	6

Accessori

Dati aziendali	
numero d'ordine	25020000004
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	