


Overview

Product information



15EDGRHD-THR-3.5-10030012022

Pluggable terminal blocks, Rated current: 10A. Rated voltage
(III/2) : 200V, pitch: 3.5mm, Color: black, Contact surface : Tin

Product advantages

- ☒ Universal installation method ensures high flexibility in equipment design
- ☒ Suitable for THR welding process

Product certification



Technical data

Product drawing

3D model

□

Packaging information

Type of packaging

box-packed

Processing notes

Process

Reflow soldering/wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

150V

Rated current (B)

10A

Rated current (C)

10A

50A

Electrical parameters IEC

Rated voltage	200V
Rated voltage(III/3)	80V
Rated current	10A
Rated voltage(III/2)	200V
Rated voltage(II/2)	320V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Pitch	3.5mm
Number of potentials	4
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Shell color	Black
Insulating material group	IIIa
Flammability rating	UL94V-0

Environmental data

Ambient temperature (operation)	-30℃~120℃(depending on derating curve)
---------------------------------	--

Accessories

Tool

Bolt driver

/

Line taking tool

/

Enclosure

Code strip

/

Bridge components

/

Marking bar

/

Else

/

Business data

Order number

10030012022

Packing unit

1100

Minimum order quantity

Products weight (without
packaging)

1.11