


## Przegląd

### Informacje o produkcie



## WS6-TW-11030000320

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 800 V, Rated current: 41 A, Number of connectors: 3, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 6 mm<sup>2</sup>, AWG: 24 - 10, Width: 8 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

### Zalety produktu

- ☑ spring-cage connection technology, good anti-vibration performance;
- ☑ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☑ Unique plug-in bridge, high circuit connection efficiency;
- ☑ Can be matched with marker strips to avoid incorrect insertion of wires.

### Certyfikacja produktu



## Dane techniczne

### Rysunek produktu

### Model 3D

□

### Wiring data

|                                   |                      |
|-----------------------------------|----------------------|
| Strip length                      | 12~13mm              |
| Conductor cross section solid     | 0.2~6mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~6mm <sup>2</sup> |
| Conductor cross section solid AWG | 24~10                |

### Environmental conditions

|                                       |                                               |
|---------------------------------------|-----------------------------------------------|
| Ambient temperature (operation)       | -40 °C ~ 105 °C (depending on derating curve) |
| Relative humidity (storage/transport) | 25%~75%                                       |

IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated voltage (III / 3) | 800V |
| Rated current (III / 3) | 41A  |
| Rated surge voltage     | 8KV  |

Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

Dimension

|                  |        |
|------------------|--------|
| NS 35/7,5 Height | 40mm   |
| End plate width  | 2.5mm  |
| NS 35/15 Height  | 47.5mm |
| length           | 92mm   |
| width            | 8mm    |
| Height           | 39.5mm |

Overview

|                                           |                             |
|-------------------------------------------|-----------------------------|
| Connection type                           | Pull back spring connection |
| Number of rows                            | 1                           |
| number of connections                     | 3                           |
| Open-end side panels                      | Yes                         |
| Insulation Materials                      | PA                          |
| Flame retardant grade, in line with UL 94 | V0                          |

Akcesoria

Marker

|            |           |
|------------|-----------|
| Top marker | ZB8 / WB5 |
|------------|-----------|

|                |                        |
|----------------|------------------------|
| Side marker    | DEK6                   |
| Marker support | DTH5-25×5 / DTH5-25×12 |
| Warning cover  | EEA6                   |

Accessories

|                                                    |          |
|----------------------------------------------------|----------|
| Slotted screwdriver size (Blade thickness x Width) | 0.8×5.5  |
| Adjacent jumper (2P)                               | WFA6     |
| Alternate jumper (2P)                              | WFB6     |
| Staggered jumper (2P)                              | /        |
| End cover                                          | D-WS6-TW |

Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

Marking & Installation

|               |       |
|---------------|-------|
| Marking strip | ZB8   |
| Marker cards  | DBE-1 |

Accessories

|           |                      |
|-----------|----------------------|
| End cover | D-WS6-TW             |
| Bridge    | WFA6                 |
| End clamp | E-WS                 |
| DIN rail  | NS35/7.5-1000-00A(H) |

Dane biznesowe

|                      |             |
|----------------------|-------------|
| numer zamówienia     | 11030000320 |
| Jednostka opakowania | 20          |

|                                 |        |
|---------------------------------|--------|
| Minimalna ilość zamówienia      | 20     |
| Waga produktów (bez opakowania) | 21.106 |