Panoramica

Informazioni sul prodotto



DGR10-10A(H)-12010000069

Transfer barrier terminal blocks,Rated current:10A.Rated voltage（UL）:600V,Cross section:24~16AWG,pitch:7.3mm,Color:black,Contact surface:Tin

Vantaggi del prodotto

☑ Screw connection for worldwide use
☑ Fence type wiring structure, stable and reliable connection
☑ Provide the cabinet and panel electrical transfer connections

Certificazione del prodotto

CE

Dati tecnici

Disegno del prodotto

Modello 3D

Connection capacity

AWG	24~16AWG
Torque	0.5N.m

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	10A
Rated current (D)	5A

Rated current (C)	10A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	slotted-phillips screwdriver
screw thread	M3
Pitch	7.3mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059

Environmental data

Ambient temperature (operation)	-40℃~125℃

Accessori

Accessories

Dati aziendali

numero d'ordine	12010000069
Unità di imballaggio	16
Quantità di ordine minimo	/
Peso dei prodotti (senza imballaggio)	39