

Panoramica

Informazioni sul prodotto



RA-EBBF-2010-F-L300-00A(H)-25040000001

Female float connector for exchange battery. Rated current: 60A; Rated voltage: 72V DC; Withstand voltage: 1500V AC; Insulation resistance > 500M Ω; Protection grade meet IP67 for female side only; Mechanical life ≥ 5000 times; Pull out force > 50N; Operating temperature: - 40 ~ 105 °C; Salt spray resistance : 72h; Flame retardant grade: UL94-v0; Environmental protection: RoHS.

Vantaggi del prodotto

- ☒ Product interoperability with positive and negative insertion function
- ☒ The floating amount when the product is inserted can compensate for the gap between the car body and the battery
- ☒ The guide post is aligned and inserted, which is convenient and quick

Certificazione del prodotto

RoHS

Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

Series

DA

DEE

DQ

DF

versions

Connection method

Spring cage connection

Female/Male

Male

Dimension	3A
	32A
	6B
	10B
	24B
	32B
Number of positions	48B
	20
	1
	24

Accessori

Dati aziendali	
numero d'ordine	25040000001
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	