Panoramica

Informazioni sul prodotto

SM-EBS-0003-F-L300-25020000008

Female connector with direct plug in and out.Rated current:2A; Rated voltage:48V DC; Withstand voltage:300V AC; Insulation resistance ＞ 30M Ω; Protection grade meet IP66 when mated; Mechanical life ≥ 100 times; Pull out force ＞ 25N; Operating temperature: - 40 ~ 105 ℃; Salt spray resistance : 48h; Flame retardant grade:UL94-v0; Environmental protection:RoHS. Color: Insert insulation - orange.

Vantaggi del prodotto

☑ Small structure and high space utilization
☑ Plug-and-play error prevention, simple interface
☑ Straight plug operation, convenient and quick
☑ Different colors of inner core insulator, easy to identify
☑Beautiful appearance, more ergonomic design

Certificazione del prodotto

RoHS

Dati tecnici

Disegno del prodotto

Modello 3D

Marking

Series	DD
	DK

versions

Connection method	Screw connection
Female/Male	Female
	16A

Dimension	6B
	10B
	16B
	24B
	48B
Number of positions	7

Accessori

Dati aziendali

numero d'ordine	25020000008
Unità di imballaggio	
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	