

Panoramica

Informazioni sul prodotto



40A-GM-2.5-92116000498

40A silver gold male pins, Adapter wire specification 2.5mm²

Vantaggi del prodotto

- ☒ High-precision turning process, stable and reliable products;
- ☒ Gold-plated and silver-plated are available, suitable for different environmental requirements;
- ☒ Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

□

Marking

classification	Contact
Series	40A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Silver plated
Material	Copper alloy

Standards

Connection meets standards	EN 60664-1 IEC 61984
----------------------------	----------------------

Technical specification

Conductor cross sections (mm²)	2.5mm²
Conductor cross sections(AWG)	14AWG
Working current	≤16A
Contact resistance	≤0.3mΩ
Plating Thickness	≥3μ"
Temperature range	-40℃~+125℃
Strip length	9mm
working life-mating cycles	≥500

Accessori

Dati aziendali

numero d'ordine	92116000498
Unità di imballaggio	100
Quantità di ordine minimo	100
Peso dei prodotti (senza imballaggio)	3.142