Panoramica

Informazioni sul prodotto



PC16-PE-11010000028

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm² - 16 mm², AWG: 12 - 4, Width: 12.2 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

Vantaggi del prodotto

☑Screw connection technology, reliable connection;
☑Grounding structure, protection circuit;
☑Copper alloy material, good corrosion resistance;
☑Can be matched with marker strips to avoid incorrect insertion of wires。

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Wiring data

Screw type	Slotted screw
Conductor cross section flexible (ferrule with plastic sleeve)	0.2-16mm²
Strip length	11~12mm
Conductor cross section solid	0.2~16mm²
Conductor cross section flexible	0.2~16mm²
Conductor cross section solid AWG	12~4
screw thread	M4

Tightening torque	1.2N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	8KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	54mm
NS 35/15 Height	61.5mm
length	42.5mm
width	12.2mm
Height	52.8mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessori

Accessories

Slotted screwdriver size (Blade thickness x Width)	1×4
Fixed bridge	/
Insertion bridge	EB2-12 / EB3-12 / EB10-12
End cover	/
Separating disk	/
Partition plate	/

Marker

Top marker	/
Marker	ZT12
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB10
Marker cards	DBE-1

Accessories

Bridge	EBXX-12
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

Dati aziendali

numero d'ordine	11010000028
Unità di imballaggio	50

Quantità di ordine minimo	50
Peso dei prodotti (senza imballaggio)	35.36