


Panoramica

Informazioni sul prodotto



PCDK4-PE-11010000120

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Number of connectors: 3, Number of potentials: 1, Cross section: 0.2 mm² - 4 mm², AWG: 24 - 10, Width: 6.2 mm, Color: green-yellow, Mounting type: NS 35/7.5, NS 35/15

Vantaggi del prodotto

- ☒ Screw connection technology, reliable connection;
- ☒ Grounding structure, protection circuit;
- ☒ Copper alloy material, good corrosion resistance;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Wiring data

Screw type	Slotted screw
2 flexible conductors with a TWIN ferrule	0.5-1.5mm ²
Strip length	7~8mm
Conductor cross section solid	0.2~4mm ²
Conductor cross section flexible	0.2~4mm ²
Conductor cross section solid AWG	24~10
screw thread	M3
Tightening torque	0.5N.m

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated surge voltage	6KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Dimension

NS 35/7,5 Height	48.3mm
NS 35/15 Height	55.8mm
length	63.5mm
width	6.2mm
Height	45.8mm

Overview

Connection method	screw connection
Number of rows	1
number of connections	4
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

Accessori

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
--	---------

Fixed bridge	/
Insertion bridge	EB2-6 / EB3-6 / EB10-6
End cover	/
Separating disk	/
Partition plate	/

Marker

Top marker	/
Marker	ZB6
Marker support	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB6
Marker cards	DBE-1

Accessories

Bridge	EBXX-6
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

Dati aziendali

numero d'ordine	11010000120
Unità di imballaggio	50
Quantità di ordine minimo	50

Peso dei prodotti (senza imballaggio)	26.05
--	-------