Panoramica

Informazioni sul prodotto

DGR60-00A(H)-12010000167

Transfer barrier terminal blocks,Rated current:80A.Rated voltage（UL）:600V,Cross section:20~4AWG,pitch:19mm,Color:black,Contact surface:Tin

Vantaggi del prodotto

☑ Screw connection for worldwide use
☑ Fence type wiring structure, stable and reliable connection
☑ Provide the cabinet and panel electrical transfer connections

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Connection capacity

AWG	20~4AWG

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	80A
Rated current (D)	5A

Electrical parameters IEC

Rated current	101A

Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M6
Pitch	19mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059

Environmental data

Ambient temperature (operation)	-40℃~125℃

Accessori

Accessories

Dati aziendali

numero d'ordine	12010000167
Unità di imballaggio	8
Quantità di ordine minimo	/
Peso dei prodotti (senza imballaggio)	83