

Panoramica

Informazioni sul prodotto



DG381A-3.81-10040002199

PCB terminal blocks, Rated current: 10A, Rated voltage (III/2) 130V, Cross section: 1.0mm², pitch: 3.81mm, connector method: Screw connector with tension sleeve, Color: green, Contact surface : Tin

Vantaggi del prodotto

- ☒ Universal connection method to ensure a high degree of flexibility in device design
- ☒ Multi-layer wire connection can achieve higher contact density
- ☒ Fixed screw connection technology, safe and reliable

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~1.0mm²

Conductor cross section flexible

0.2~1.0mm²

AWG

26~16AWG

Torque

0.2N.m

Strip length

6mm

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	12A

Electrical parameters IEC

Rated voltage	130V
Rated current	10A
Rated voltage(III/2)	130V
Rated power frequency voltage(1min)	1.25KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.81mm
Number of potentials	4
Pluggable or not	no
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification

UL1059/IEC60998

Environmental data

Ambient temperature (operation)

-40°C~105°C

Accessori

Accessories

Coding strip

/

Bridge

DG032-3.81

Marking strip

/

Others

/

Tool

Operating tool

/

Screwdriver

0.4x2.5mm, Slotted screwdriver

Dati aziendali

numero d'ordine

10040002199

Unità di imballaggio

560

Quantità di ordine minimo

30

Peso dei prodotti (senza
imballaggio)

2.5