


Panoramica

Informazioni sul prodotto

**SR-M12A-04P-FF-SF7003-20030000375**

Sensor/Actuator Female socket,M12,Coding A,Unshielded,Rear panel installation/M12*1.0 Thread mounted,90° horizontal pins

Vantaggi del prodotto

- ✓ Sealing optimization, protection level up to IP67
- ✓ Meet the harsh environment
- ✓ Suitable for various occasions connection technology
- ✓ Compatible with the international and domestic same series products

Certificazione del prodotto

**RoHS****REACH**

Dati tecnici

Disegno del prodotto

Modello 3D

□

Environmental conditions

Ambient temperature

-40°C...105°C

IP class

IP67

General parameters

Rated current

4A

250V

Number of potentials

4

Insulation resistance

≥ 100 MΩ

Error-proof coding

A-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering pin
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Rear board installation

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-101
--------------------------	-----------------

Accessori

Accessories

Sealing cap	CAP-M12-MP-8003
-------------	-----------------

Dati aziendali

numero d'ordine	20030000375
Unità di imballaggio	/
Quantità di ordine minimo	100
Peso dei prodotti (senza imballaggio)	/

