DEGSON

Panoramica

Informazioni sul prodotto

SPSH-M12X-08P-FF-SH7002-20030001331

Sensor/Actuator Female socket,M12,Coding X,Shielded,Front panel installation/M16*1.5 Thread mounted,180° vertical pins

Vantaggi del prodotto

☑Sealing optimization, protection level up to IP67
☑Meet the harsh environment
☑Suitable for various occasions connection technology
☑Compatible with the international and domestic same series products

Certificazione del prodotto

RoHS REACH

Dati tecnici

Disegno del prodotto

Modello 3D

Environmental conditions

Ambient temperature	-20℃...105℃
IP class	IP67

General parameters

Rated current	0.5A
	50V
Number of potentials	8
Insulation resistance	≥ 100 MΩ
Error-proof coding	X-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering pin
Insertion and pullout cycle	≥ 100
Torque	0.4 Nm
Type of installation	Installation in front of the board

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Zinc alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-109

Accessori

Accessories

Sealing cap	CAP-M12-MP-8003

Dati aziendali

numero d'ordine	20030001331
Unità di imballaggio	/
Quantità di ordine minimo	100
Peso dei prodotti (senza imballaggio)	/