

Panoramica

Informazioni sul prodotto



DGP95-10090000017

Through-wall terminal blocks, Rated current: 232A. Rated voltage
(III/3) : 1000V, Width: 25.0mm, Color: gray, Contact surface : Tin

Vantaggi del prodotto

- ☑ Screw connection technology, safe and reliable
- ☑ Through-wall installation, free positioning

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Connection capacity

Conductor cross section solid	25~95mm ²
Conductor cross section flexible	25~95mm ²
AWG	4~4/0AWG
Strip length	27mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	230A

Rated current (D)	5A
Rated current (C)	230A

Electrical parameters IEC

Rated voltage(III/3)	1000V
Rated current	232A
Rated surge voltage(III/3)	8KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Hexagon screwdriver
screw thread	M8
Pitch	25mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Accessori

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Dati aziendali

numero d'ordine	10090000017
Unità di imballaggio	10
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	293