Panoramica

Informazioni sul prodotto



DGH50-10090000013

Through-wall terminal blocks,Rated current:150A.Rated voltage（III/2）:1000V,Width:18.8mm,Color:gray,Contact surface :Tin

Vantaggi del prodotto

☑ Screw connection technology,safe and reliable
☑ Through-wall installation, free positioning

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Connection capacity

Conductor cross section solid	16~50mm²
Conductor cross section flexible	16~50mm²
AWG	6~2/0AWG
Strip length	24mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	170A

Rated current (D)	5A
Rated current (C)	170A

Electrical parameters IEC

Rated voltage(III/3)	690V
Rated current	
	150A
Rated voltage(III/2)	1000V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	8KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M6
Pitch	18.8mm
Number of potentials	1
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated

Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessori

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Dati aziendali

numero d'ordine	10090000013
Unità di imballaggio	20
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	120