

## Panoramica

## Informazioni sul prodotto

**WSF4-TA-08A(H)-11030000564**

Spring-cage type Din-Rail TB, connector method: Spring-cage/plug-in connector, Rated voltage: 24 V, Rated current: 6.3 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup>- 4 mm<sup>2</sup>, AWG: 28 - 12, Width: 6 mm, Fuse type: Glass / ceramics / ..., Fuse type: G / 5 x 20, Color: black, Suitable for 24 V DC LED, Mounting type: NS 35/7.5, NS 35/15.

## Vantaggi del prodotto

- ☒ WS Fuse wire terminal;
- ☒ spring-cage connection technology, good anti-vibration performance;
- ☒ Use an ordinary flat-blade screwdriver, you can easily wire and take the wire;
- ☒ Unique plug-in bridge, high circuit connection efficiency;
- ☒ Can be matched with marker strips to avoid incorrect insertion of wires.

## Certificazione del prodotto



## Dati tecnici

## Disegno del prodotto

## Modello 3D

☐

## Wiring data

|                                   |                      |
|-----------------------------------|----------------------|
| Strip length                      | 10~12mm              |
| Conductor cross section solid     | 0.2~4mm <sup>2</sup> |
| Conductor cross section flexible  | 0.2~4mm <sup>2</sup> |
| Conductor cross section solid AWG | 28~12                |

## Environmental conditions

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Ambient temperature (operation) | -40 °C ~ 105 °C (depending on derating curve) |
|---------------------------------|-----------------------------------------------|

|                                       |         |
|---------------------------------------|---------|
| Relative humidity (storage/transport) | 25%~75% |
|---------------------------------------|---------|

#### IEC Electrical parameters

|                         |      |
|-------------------------|------|
| Rated current (III / 3) | 6.3A |
|-------------------------|------|

#### Environmental protection

|            |                                 |
|------------|---------------------------------|
| REACH SVHC | Lead 7439-92-1                  |
| RoHS       | No excessive harmful substances |

#### Dimension

|                  |        |
|------------------|--------|
| NS 35/7,5 Height | 68mm   |
| NS 35/15 Height  | 75.5mm |
| length           | 60mm   |
| width            | 6mm    |
| Height           | 66.6mm |

#### Overview

|                                           |                             |
|-------------------------------------------|-----------------------------|
| Connection type                           | Pull back spring connection |
| Number of rows                            | 1                           |
| number of connections                     | 2                           |
| Open-end side panels                      | no                          |
| Insulation Materials                      | PA                          |
| Flame retardant grade, in line with UL 94 | V0                          |
| fuse                                      | G/5 x 20                    |
| Fuse type                                 | Glass/ceramic/...           |

#### Accessori

##### Marker

|            |     |
|------------|-----|
| Top marker | ZB6 |
|------------|-----|

|                |      |
|----------------|------|
| Side marker    | /    |
| Marker support | /    |
| Warning cover  | EEA4 |

#### Accessories

|                                                    |         |
|----------------------------------------------------|---------|
| Slotted screwdriver size (Blade thickness x Width) | 0.5×3.5 |
| Adjacent jumper (2P)                               | WFA4    |
| Alternate jumper (2P)                              | WFB4    |
| Staggered jumper (2P)                              | /       |
| End cover                                          | /       |

#### Installation

|                               |                                       |
|-------------------------------|---------------------------------------|
| End clamp                     | E-WS N / E-PC-1100A                   |
| Terminal strip marker support | KLM3-20x8 / KLM3-44x8 / DBE-1 / DBE-2 |
| DIN rail                      | NS35/7.5-1000-00A(H)                  |

#### Dati aziendali

|                                       |             |
|---------------------------------------|-------------|
| numero d'ordine                       | 11030000564 |
| Unità di imballaggio                  | 115         |
| Quantità di ordine minimo             | 115         |
| Peso dei prodotti (senza imballaggio) | 13.69       |