


Aperçu

Informations sur le produit



15EDGVC-THR-3.81-10030000858

Pluggable Terminal Blocks nominal current 8A. Rated voltage (II/2): 250V, pitch: 3.81mm, Color: black, Contact surface: Tin

Les avantages des produits

- ☒ Suitable for SMT welding process
- ☒ The plug direction is perpendicular to PCB, Can meet the needs of different connectors

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

8A

Electrical parameters IEC

Rated voltage

250V

Rated current

8A

Rated voltage(III/2)

250V

Rated surge voltage(III/2)

2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	3.81mm
Number of potentials	7
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~130°C
---------------------------------	-------------

Accessoires

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Caractéristiques commerciales

Numéro de la commande	10030000858
Unité d'emballage	
Quantité minimale de commande	
Le poid de produit (sans emballage)	