## Overview

### Product information

# D10A-SF-1L-CV-M20-21010000169

10A Lower base,single buckle,back cover ,side entry,M20 Thread hole,Wear protective cover

### Product advantages

☑Metal or high-strength plastic material, resistant to high-strength mechanical shock；
☑Various installation methods and outlet directions to meet on-site wiring requirements；
☑Snap-in combination structure, dustproof, waterproof, easy operation；

### Product certification

## Technical data

### Product drawing

### 3D model

### Marking

| | |
|---|---|
| classification | Upper Housing/base |
| Series | A |
| Type | Surface mount base |
| Description | With plastic dust cover |
| Specification | Low structure |

### Versions

| | |
|---|---|
| Dimension | 10A |
| locking Category | Single lock |
| Thread specification | 1x M20 |

### Material characteristics

| | |
|---|---|
| Flammability rating | V-0 |
| RoHS | conform |
| Material (upper housing/base) | Die-cast aluminium alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey（RAL 7037） |
| Material (seal) | NBR |
| Material (lock catch) | Zinc plated |

Technical specification

| | |
|---|---|
| Limiting temperatures | -40℃~+125℃ |
| IP class | IP65 |

## Accessories

## Business data

| | |
|---|---|
| Order number | 21010000169 |
| Packing unit | 100 |
| Minimum order quantity | 1 |
| Products weight (without packaging) | 182.6 |