Panoramica

Informazioni sul prodotto



15EDGA-3.5-10020000001

Pluggable terminal blocks,Rated current:7A.Rated voltage （III/2）:250V,pitch:3.5mm,Color:green,Contact surface :Tin

Vantaggi del prodotto

☑ PCB welding, plug direction is parallel to the PCB
☑ Multiple contacts to provide touch protection for connection

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Processing notes

Process	Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated current (B)	8A

Electrical parameters IEC

Rated voltage	250V
Rated voltage(III/3)	160V
Rated current	7A
Rated voltage(III/2)	250V

Rated voltage(II/2)	320V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Pitch	3.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	Ⅰ
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessori

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Dati aziendali

numero d'ordine	10020000001
Unità di imballaggio	3575
Quantità di ordine minimo	30
Peso dei prodotti (senza imballaggio)	0.6