

Panoramica

Informazioni sul prodotto

**8EDGVC-7.5-10030002934**

Pluggable terminal blocks, Rated current: 20A. Rated voltage
(III/3) : 400V, pitch: 7.5mm, Color: gray, Contact surface : Tin

Vantaggi del prodotto

- ✓ Universal installation method to ensure a high degree of flexibility in device design
- ✓ The plug direction is perpendicular to PCB

Certificazione del prodotto



Dati tecnici

Disegno del prodotto

Modello 3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A
Rated current (C)	15A

Electrical parameters IEC

Rated voltage	400V
Rated voltage(III/3)	400V
Rated current	20A
Rated surge voltage(III/3)	4KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	7.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accessori

Tool

Screwdriver

/

Operating tool

/

Accessories

Coding strip

DG015

Bridge

/

Marking strip

/

Others

/

Dati aziendali

numero d'ordine

10030002934

Unità di imballaggio

1600

Quantità di ordine minimo

30

Peso dei prodotti (senza
imballaggio)

0.85