Panoramica

Informazioni sul prodotto



15EDGK-3.5-10010000037

Pluggable terminal blocks,Rated current:7A.Rated voltage （II/2）:250V,pitch:3.5mm,Color:green,Contact surface :Tin

Vantaggi del prodotto

☑ Adapt to multi-type sockets, device design is highly flexible
☑ Keying requirements can be met
☑ Universal installation method, suitable for various situations

Certificazione del prodotto

Dati tecnici

Disegno del prodotto

Modello 3D

Connection capacity

Conductor cross section solid	0.5~1.5mm²
Conductor cross section flexible	0.5~1.5mm²
AWG	28~16AWG
Torque	0.2N.m
Strip length	7mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	8A

Rated current (D)	8A

Electrical parameters IEC

Rated voltage	250V
Rated current	7A
Rated voltage(II/2)	250V
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059

Environmental data

Ambient temperature (operation)	-40℃~105℃

Accessori

Tool

Screwdriver	0.4x2.5,Slotted screwdriver
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Dati aziendali

numero d'ordine	10010000037
Unità di imballaggio	200
Quantità di ordine minimo	
Peso dei prodotti (senza imballaggio)	2.84