

Overview

Product information



Relay Socket-DSRC-05A-F3-00A(H)-30020000063

DSRC Relay Socket, used for 1PDT relay, screw connection

Product advantages

- ☒ Screw relay socket
- ☒ Safe isolation between coil and contacts
- ☒ 10A ,1PDT
- ☒ Separation of input & output

Product certification



Technical data

Product drawing

3D model

□

Dimension

width	16mm
length	80mm
Depth including bracket	61.5mm

Environmental data

Ambient temperature (operation)	-45°C ~ +85°C
Ambient temperature (storage / transport)	-40°C ~ +65°C

Technical data

Rated voltage UN	300V
------------------	------

Rated current IN	12A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

Connection data 1

Connection name	enter
Connection method	Screw connection
Stripping length	7-8mm
screw thread	M3
Cross section of flexible conductor	0.5-2.5mm²
Connectable guide cross section AWG	20-14AWG

Connection data 2

Connection name	Output
Stripping length	7-8mm
Cross section of flexible conductor	0.5-2.5mm²
Connectable guide cross section AWG	20-14AWG
Connection method	Screw connection

Accessories

Accessory

Bridge	DFB2-15-13-00Z(H)
Function Module	DMD-L-6/24V-00A(H)

Business data

Order number	30020000063
Packing unit	10 SKT

Minimum order quantity	10 SKT
Products weight (without packaging)	22g