

Przegląd

Informacje o produkcie

**D32A-SF-4g-CV-2PG29-21010000385**

32A Lower base, Four levers, back cover, side entry, double PG29 Thread hole, Wear protective cover

Zalety produktu

- ✓ Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- ✓ Various installation methods and outlet directions to meet on-site wiring requirements;
- ✓ Snap-in combination structure, dustproof, waterproof, easy operation;

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D



Marking

classification	Upper Housing/base
Series	A
Type	Surface mount base
Description	With plastic dust cover
Specification	Low structure

versions

Dimension	32A
locking Category	Double lock
Thread specification	2x PG29

Material characteristics

Flammability rating	V-0
RoHS	conform
Material (upper housing/base)	Die-cast aluminium alloy
Material(upper housing/base)	spray
Color (upper housing/base)	Grey (RAL 7037)
Material (seal)	NBR

Technical specification

Limiting temperatures	-40°C~+125°C
IP class	IP65

Akcesoria

Dane biznesowe

numer zamówienia	21010000385
Jednostka opakowania	100
Minimalna ilość zamówienia	1
Waga produktów (bez opakowania)	388