## Overview

### Product information

# DT22MU-10C-31010000444

φ22mm Contact module, Color: black, Contact type: one normally open

### Product advantages

☑ The shell is made of zinc alloy metal material, with good wear resistance and room temperature mechanical properties
☑ Adopt modular design to meet customers' requirements for installation convenience, use flexibility, product durability and so on
☑ The button head and the middle seat are fixed with screws, which has stronger anti-impact, anti-drop, anti-vibration and other properties

### Product certification

CE

## Technical data

### Product drawing

### 3D model

### General parameters

| | |
|---|---|
| Insulation resistance | ≥ 100 MΩ |

### Technical specification

| | |
|---|---|
| Power frequency withstand voltage | 1890VAC/50Hz/60s |
| Impact resistance | Button 70g, Mushroom head button 15g, Select switch 200g |
| Environment humidity | 45-85%RH |
| Vibration resistant | 1.0mm/50HZ |
| Mechanical life | ≥ 2 million times |

| | |
|---|---|
| Electrical life | ≥ 200,000 times |
| Nominal insulation voltage | 440V |
| Conventional heating current | 10A |
| Contact resistance | ≤50mΩ |

Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -25 °C ... 55 °C |

## Accessories

## Business data

| | |
|---|---|
| Order number | 31010000444 |
| Packing unit | 10 |
| Minimum order quantity | 10 |
| Products weight (without packaging) | |