Visión general

Información del Producto



Relay module-DM50-RMUS-04-PN-1-44-00A(H)-30030000107

Subminiature Relay Module,with relay Socket ,4 relays can be installed,with relay Socket,with indicator light,panasonic relay,PNP or NPN signal can be input (Please contact us for relay replacement)

Ventajas del producto

☑ Each signal channel and power supply voltage have LED status indicators
☑ Pluggable subminiature relay, with a set of normally open contacts, one-to-one output at the output
☑ Suitable for NPN, PNP controller
☑ Freewheeling diode for each signal path
☑ Compact size, saving space in the cabinet

Certificación del producto

Datos técnicos

Dibujo del producto

Modelo 3D

Overview

Installation location	Arbitrary
Number of channels	4
Shell Insulation Materials	PC
color	black

Dimension

length	65.6mm
width	60mm
Height	31mm

Environmental data	
Ambient temperature (operation)	-20 °C ... 70 °C
Ambient temperature (storage / transport)	-20 °C ... 70 °C

Standards/Regulations	
Standards/Regulations	IEC61810
Pollution level	3
Overvoltage category	III

Output technical data	
Contact type	1NO
Maximum switching voltage	240VAC 30VDC
Limit continuous current	5A
Fault monitoring (open circuit/short circuit)	no

Output connection data	
Connection name	Output
Connection method	Screw connection
Stripping length	6-7mm
screw thread	M3
Connection volume	1
Number of digits	8
Hard wire cross section	1.0 ... 2.5mm²
Cross section of flexible conductor	1.0 ... 2.5mm²
Connectable guide cross section AWG	28 ... 12AWG

Enter connection data	
Rated input voltage	24VDC
Relative to UN input voltage range	0.9....1.1

Protected name	Polarity protection
Protection circuit/component	Polarity protection diode
Status display/channel	green
Connection name	input
Connection method	screw connection
Stripping length	6-7mm
screw thread	M3
Connection volume	1
Number of digits	6
Hard wire cross section	1.0 ... 2.5mm²
Cross section of flexible conductor	1.0 ... 2.5mm²
Connectable guide cross section AWG	28...12AWG

Accesorios

Datos empresariales

Número de pedido	30030000107
Unidad de embalaje	2
Cantidad mínima de pedido	10
Peso del producto (sin embalaje)	80