
概要

製品情報



DK-4/0-F-21020000123

Heavy-duty insert,Number of contacts:4/0+PE,Dimension:16B,Rated voltage :690V,Rated current:80A,Female insert,Screw connector

製品の特長

☑Screw connection technology, applicable to a wide range of wire specifications；
☑No need special tools,easy to operate；
☑Less materials, easy to manage；
☑With grounding protection。

製品認証

CE

技術データ

製品チャート

3Dモデル

Marking

classification	Insert
Series	DK

Versions

Connection method	Screw connection
Female/Male	Female
Dimension	16B
Number of positions	4/0
PE Contacts	Yes

Material characteristics

Material（insert）	Polycarbonate（PC）
Materia（Contact）	Copper alloy
Surface（Contact）	Silver plated
Flammability rating	V-0
color	Grey/White（RAL 7032）
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	80A
	690V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	14mm
Rated torque	1.2N.m(1.5mm²) 2N.m(2.5mm²) 3N.m(4/6/10/16mm²)
Conductor cross sections（mm²）	1.5-16mm²
Conductor cross sections(AWG)	16-6AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984

アクセサリ

Accessories

Screwdriver	/

ビジネスデータ

注文番号	21020000123
パッキングユニット	100
最小注文数量	5
1個あたりの重量（梱包を含めない）	115