
概要

製品情報



DK-8/0-M-21020000061

Heavy-duty insert,Number of contacts:8/0+PE,Dimension:24B,Rated voltage :690V,Rated current:100A,Male insert,axial Screw connector

製品の特長

☑Axial Screw connection technology, applicable to a wide range of wire specifications;
☑Less materials, easy to manage;
☑With grounding protection。

製品認証

CE

技術データ

製品チャート

3Dモデル

Marking

classification	Insert
Series	DK

Versions

Connection method	Axial screw connection
Female/Male	Male
Dimension	24B
Number of positions	8/0
PE Contacts	Yes

Material characteristics

Material（insert）	Polycarbonate（PC）
Materia（Contact）	Copper alloy
Surface（Contact）	Silver plated
Flammability rating	V-0
color	Grey/White（RAL 7032）
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	100A
	690V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.5mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Strip length	13mm
Rated torque	6N.m(10mm²) 6N.m(16mm²) 7N.m(25mm²)
Conductor cross sections（mm²）	10-25mm²
Conductor cross sections(AWG)	7-3AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984

アクセサリ

Accessories

Screwdriver	/

ビジネスデータ

注文番号	21020000061
パッキングユニット	100
最小注文数量	5
1個あたりの重量（梱包を含めない）	304.44