## Panoramica

### Informazioni sul prodotto



# DG252-10080000069

Feed through terminal blocks,Rated current:17.5A.Rated voltage（III/2）:450V,pitch:10.0mm,Color:White,Contact surface :Zn

### Vantaggi del prodotto

☑ Multiple wiring holes for current distribution
☑ Panel mounting, suitable for various situations
☑ Can realize horizontal wire-to-wire connection

### Certificazione del prodotto

VDE

## Dati tecnici

### Disegno del prodotto

### Modello 3D

### Connection capacity

| | |
|---|---|
| Conductor cross section solid | 0.5~1.5mm² |
| AWG | 22~16AWG |
| Torque | 0.8N.m |
| Strip length | 7mm |

### Electrical parameters UL

| | |
|---|---|
| Rated voltage (B) | 300V |
| Rated current (B) | 10A |

### Electrical parameters IEC

| | |
|---|---|
| | |

| | |
|---|---|
| Rated current | 17.5A |
| Rated voltage(III/2) | 450V |
| Rated power frequency voltage(1min) | 2.5KV |

Item properties

| | |
|---|---|
| Type of installation | panel |
| Connection method | Screw connection |
| Screwdriver | Slotted screwdriver |
| screw thread | M3.5 |
| Pitch | 10mm |
| Number of potentials | 12 |
| Pluggable or not | no |

Material data

| | |
|---|---|
| Environmental items | Compliant with REACH/RoHS |
| Contact material | steel |
| Contact point metal surface | Galvanized |
| Insulation Materials | PA66 |
| Flammability rating | UL94V-2 |

Mechanical tests

| | |
|---|---|
| Test Specification | UL1059/IEC60998 |

Environmental data

| | |
|---|---|
| Ambient temperature (operation) | -40℃~105℃ |

## Accessori

Accessories

| | |
|---|---|
| Coding strip | / |

| | |
|---|---|
| Bridge | / |
| Marking strip | / |
| Others | / |

Tool

| | |
|---|---|
| Operating tool | / |
| Screwdriver | / |

Dati aziendali

| | |
|---|---|
| numero d'ordine | 10080000069 |
| Unità di imballaggio | 100 |
| Quantità di ordine minimo | 30 |
| Peso dei prodotti (senza imballaggio) | 30 |